

With its high output and flexible design features, the VHP M100X is one of the most versatile pharmaceutical grade Biodecontamination Units on the market today for applications requiring an integrated solution.



VHP® M100X Biodecontamination Unit

Easy Operation	 Select from any of the saved Customer validated Biodecontamination Cycles and OptiaPhase software technology does the rest.^{1,2} 				
Productivity	 With 2 to 25g/min of hydrogen peroxide sterilant injection and OptiaPhase software control, decontaminate Enclosures as large as 300m³. VHP process technology improves cycle time. USB port allows for permanent electronic cycle data capture. 				
Integration	 Capable of operating as a standalone unit or integrated with another control system via optional Ethernet, Profinet, and/or discrete I/O. 				
Security	Operator, Supervisor, and Service user levels with password protection.				
Efficiency	 Proprietary Vaprox® Hydrogen Peroxide Sterilant minimizes risk of equipment damage and is biodegradable into water vapor and oxygen. 				
Base Unit Includes	VHP M100XAllen Bradley or Siemens HMI/PLCPower Cord	DocumentationVH2O2 Input/Output Hoses/Connections			
Applications	IsolatorsDecon ChambersWashersAHS/HVAC System Integration	Room DecontaminationPass Through ChambersSterilizers			

TECHNICAL SPECIFICATIONS

	Controller	Input Power	Class	Input Current Amps	Output Range g/min	Dimensions HxWxD in (mm)	Net Weight lbs (kg)
P	Allen Bradley	120V/10/60Hz	UL CSA	15		31 x 26 x 9	160
	Siemens	230V/1 0 /50-60Hz	UL CSA CE	15	2 – 25	(787 x 660 x 229)	(72)

Accessories

Munters Dehumidifiers

Dehumidification units available for permanent installation and portable operation.

Dräger H2O2 Sensors

Hydrogen peroxide vapor sensors available for permanent installation and portable operation.

Sterility Assurance Products

VHP Sterilant

Vaprox® Hydrogen Peroxide Sterilant

35% stabilized aqueous solution of hydrogen peroxide designed for use with VHP Biodecontamination Units and Accessories (EPA Reg. No. 58779-4).

Chemical Indicators

Steraffirm® PCC051

Chemical indicator designed for use with STERIS's VHP process technology at low to intermediate hydrogen peroxide vapor concentrations.

Steraffirm® PCC060

Chemical indicator designed for use with STERIS's VHP process technology at intermediate to high hydrogen peroxide vapor concentrations.

Biological Indicators

Spordex® NA333

E6 Geobacillus stearothermophilus (ATCC 12980) inoculated stainless steel coupon in Tyvek® designed for use with STERIS's VHP process technology.

Spordex® NA114

Culture media designed for use with Spordex biological indicators.

Spordex® NA117

Culture media designed for use with Spordex® biological indicators.



STERIS CORPORATION 5960 Heisley Road Mentor, OH 44060, USA T +1 800 444 9009

www.STERISLifeSciences.com

STERIS Offices Worldwide

Asia Pacific	+65 (0) 68 41 7677			
Canada	+1 800 444 9009			
Finland	+358 9 25851			
France	+33 (0) 2 38 84 85 40			
Germany	+49 (0) 221 466120			
Italy	+39 (0) 2 21303 424			
Latin America	+1 800 444 9009			
Spain	+34 (0) 916 585 920			
United Kingdom	+44 (0) 1256 840400			

STERIS Life Sciences

For over 100 years, STERIS has been known as a global leader, trusted partner and solutions provider in the field of sterilization and contamination control. Today, STERIS continues building on this heritage by advancing the Science of sterilization, cleaning and infection control while offering Solutions that meet our Customers' needs and high standards. STERIS is dedicated to helping you enhance the Life of your patients and the life of your equipment. From Formulated Chemistries, to Capital Equipment, and to Parts and Services, STERIS Life Sciences is your Solutions provider.

© 2017 STERIS Corporation All rights reserved No part of this publication may be reproduced in any material form without the permission of STERIS Corp.

¹ Refer to the Vaprox Hydrogen Peroxide Sterilant or package label and insert for additional information and application instructions.

² Refer to the VHP M100X Operator Manual for additional information and application instructions.

³ Siemens models only.